

Product Information

| Product Model | JFC-C |
|---------------|--|
| Product Type | Ceiling-Wall Expansion Joint Cover |
| Material | Aluminum Alloy 6063 T6, EPDM Rubber Gaskets |
| Finish | Mill finish |
| Gasket colors | Black, Grey, Beige |

Introducing our JFC-C Ceiling-Wall Expansion Joint Profile – a sleek and versatile solution compatible with various false ceiling types. Crafted from Aluminum with a smooth rubber appearance, this screwless profile combines aesthetics with practicality, offering easy installation and universal compatibility.

Features and Benefits



Durable Aluminum Brackets

Ensures long-lasting performance and structural integrity.



EPDM Rubber insert

Provides excellent flexibility, allowing the profile to adapt to varying conditions without cracking or deteriorating.



Easy Installation

Simplifies the installation process, saving time and labor costs.



Applicability

Compatible with various false ceiling types and board thicknesses.




Low Maintenance

Requires minimal upkeep, reducing ongoing operational costs and maintenance efforts.


Maintenance

- > Regularly inspect the expansion joint cover for signs of damage or wear.
- > Clean with mild soap and water as needed to maintain appearance.

| Code | Gap width A(mm) | Visible width B(mm) | Total movement (mm) |
|----------|--------------------|------------------------|------------------------|
| JFC 25C | 25 | 44 | 10mm (+5 -5) |
| JFC 35C | 35 | 54 | 15mm (+7.5 -7.5) |
| JFC 50C | 50 | 69 | 30mm (+15 -15) |
| JFC 75C | 75 | 94 | 40mm (+20 -20) |
| JFC 100C | 100 | 119 | 50mm (+25 -25) |
| | | | |







| Length | Standard length: 3 meters. |
|--------------|---|
| Fire Rating | ASTM E84 Class A. |
| Installation | Please follow the installation instructions provided in the J-CAP installation guide. |

