

Product Information

Product Model	JWS-C
Product Type	Wall-Corner Expansion Joint Cover/Seismic Profile
Material	Aluminum Alloy 6063 T6
Finish	Mill finish

The JWS-C Seismic Expansion Joint Cover is crafted to offer a smooth and visually appealing resolution for seismic expansion joints. Highlighting an aluminum center plate that can be powder-coated to harmonize with your preferred wall finish, it enriches the overall aesthetics of your space. Moreover, the incorporation of rubber gaskets ensures a smooth connection with the walls, preventing any scratches during movement.

Features and Benefits

Seismic Movement Capability

Designed to accommodate horizontal and vertical movements caused by seismic activity.

Durable Construction

Made from high-strength aluminum alloy for exceptional durability and long service life.

Easy Installation

Quick and hassle-free installation process with clear instructions provided.


Versatile Weather Endurance

Engineered with corrosion-resistant properties, this expansion joint cover is well-suited for indoor and outdoor applications.

Maintenance

- > Regularly inspect the expansion joint cover for signs of damage or wear.
- > Clean with mild soap and water as needed to maintain appearance.

Code	Gap width A(mm)	Visible width B(mm)	Total movement (mm)
JWS 100C	100	208	130mm (+80 -50)
JWS 150C	150	258	180mm (+80 -100)
JWS 200C	200	308	230mm (+80 -150)
JWS 250C	250	358	280mm (+80 -200)
JWS 300C	300	408	330mm (+80 -250)
JWS 400C	400	508	430mm (+80 -350)









Length	Standard length: 3 meters.
Fire Rating	ASTM E84 Class A.
Installation	Please follow the installation instructions provided in the J-CAP installation guide.



-0||