

Product Information

Product Model	WPS-C
Product Type	Wall-Wall (Corner) Expansion Joint Cover/seismic Profile
Material	Aluminum Alloy 6063 T6
Finish	Mill finish

Introducing our WPS Wall (Corner) Seismic Expansion Joint Cover Profile, meticulously designed to ensure optimal durability and performance.

Features and Benefits

Seismic Movement Capability

Designed to accommodate horizontal and vertical movements caused by seismic activity.



Aesthetics

Its sleek aluminum design seamlessly integrates with surrounding structures, maintaining a visually appealing environment.



Easy Installation

Quick and hassle-free installation process with clear instructions provided.

Versatile Weather Endurance


Engineered with corrosion-resistant properties, this expansion joint cover is well-suited for indoor and outdoor applications.


Maintenance

> Regularly inspect the expansion joint cover for signs of damage or wear.

> Clean with mild soap and water as needed to maintain appearance.

C	Code	Gap width A(mm)	Visible width B(mm)	Installation height C(mm)	Thermal movement (mm)	Siesmic movement (mm)
V	VPS 25C	25	72.5	18	30mm (+15 -15)	65mm (+40 -25)
V	VPS 35C	35	82.5	18	50mm (+25 -25)	75mm (+40 -35)
V	VPS 50C	50	97.5	18	80mm (+40 -40)	95mm (+45 -50)
V	VPS 75C	75	122.5	18	100mm (+40 -60)	120mm (+45 -75)
V	VPS 100C	100	160	18	115mm (+55 -60)	160mm (+60 -100)
V	VPS 150C	150	205	18	150mm (+50 -100)	205mm (+55 -150)
V	VPS 200C	200	255	18	200mm (+50 -150)	255mm (+55 -200)
V	VPS 250C	250	305	18	250mm (+50 -200)	305mm (+55 -250)









Length	Standard length: 3 meters.		
Fire Rating	ASTM E84 Class A.		
Installation	Please follow the installation instructions provided in the J-CAP installation guide.		

