

Wall - Corner Expansion Joint

Product Information

Product Model	WZB-U
Product Type	Wall - Corner Expansion Joint Cover
Material	Aluminum Alloy 6063 T6, EPDM Rubber Gaskets
Finish	Mill finish
Gasket colors	Black, Grey, Beige

Features and Benefits



Durable Aluminum Brackets
Ensures long-lasting performance and structural integrity.



EPDM Rubber insert
Provides excellent flexibility, allowing the profile to adapt to varying conditions without cracking or deteriorating.



Weather-Resistant:
Suitable for outdoor applications, as it can withstand extreme temperatures, UV exposure, and moisture, preventing corrosion and decay. For outdoor use, a water barrier must be incorporated to ensure optimal performance.



Easy Installation:
Simplifies the installation process, saving time and labor costs.



Versatile Applications
Suitable for a wide range of applications in construction.







Low Maintenance
Requires minimal upkeep, reducing ongoing operational costs and maintenance efforts.

Maintenance

- Regularly inspect the expansion joint cover for signs of damage or wear.
- Clean with mild soap and water as needed to maintain appearance.

Code	Gap width A(mm)	Visible width B(mm)	Installation height C(mm)	Installation width D(mm)	Total movement (mm)
WZB 25U	25	31	18	80	10mm (+5 -5)
WZB 35U	35	41	18	90	14mm (+7 -7)
WZB 50U	50	56	18	105	20mm (+10 -10)
WZB 75U	75	81	18	130	30mm (+15 -15)



Length Standard length: 3 meters.

Fire Rating ASTM E84 Class A.

Installation Please follow the installation instructions provided in the J-CAP installation guide.